

**2017 Chevrolet Truck 3500 LCF Gas STANDARD EQUIPMENT**

S = Standard Equipment A = Available -- (dashes) = Not Available D = ADI Available  
 ■ = Included in Equipment Group □ = Included in Equipment Group but upgradeable

\*Indicates availability of feature on multiple models. For example, it indicates feature availability on 2WD and 4WD Models or Rear wheel drive and All-wheel drive Models.

Codes listed in the shaded column titled Ref. Only RPO Code are for internal use only and should not be ordered.

Free Flow RPO Code	Ref. Only RPO Code	Description	Reg. Cab				Crew Cab	
			CP11003 109" WB 1WT	CP12003 132.5" WB 1WT	CP13003 150" WB 1WT	CP14003 176" WB 1WT	CP13043 150" WB 1WT	CP14043 176" WB 1WT
	C60	<b>Air conditioning</b> , single-zone manual, integral in-dash mounted	S	S	S	S	S	S
	K34	<b>Cruise control</b> , electronic, automatic	S	S	S	S	S	S
		<b>Cup holders</b>	S	S	S	S	S	S
	UIY	<b>Audio system</b> , AM/FM stereo with CD player, auxiliary input and USB Port	S	S	S	S	S	S
	UAD	<b>Audio system feature</b> , 2 speakers	S	S	S	S	S	S
	AU3	<b>Door locks</b> , power	S	S	S	S	S	S
	UDH	<b>Driver Information Center</b>	S	S	S	S	S	S
		<b>Floor mats</b>	S	S	S	S	S	S
		<b>Lighting</b> , interior dome	S	S	S	S	S	S
	A1F	<b>Seat</b> , front high back bucket driver and passenger, tricote cloth covered reclining highback driver seat with single two occupant fold down passenger seat	S	S	S	S	S	S
	N3R	<b>Steering wheel</b> , urethane	S	S	S	S	S	S
	N33	<b>Steering column</b> , Tilt-Wheel	S	S	S	S	S	S
		<b>Storage</b> , door pockets	S	S	S	S	S	S
		<b>Storage</b> , seatback pockets	S	S	S	S	S	S
	A31	<b>Windows</b> , power	S	S	S	S	S	S
		<b>Windshield washer bottle access</b> , on passenger side dash when passenger-side door is open	S	S	S	S	S	S
		<b>Daytime Running Lamps</b>	S	S	S	S	S	S
		<b>Glass</b> , tinted	S	S	S	S	S	S
	DB5	<b>Mirror</b> , outside driver and front passenger, wide load with integral arm	S	S	S	S	S	S
	E01	<b>Assist steps</b>	S	S	S	S	S	S
	2TA	<b>Tires</b> , front, LT215/85R16 E 115/112 L BW ALS VAR1, LRR (low rolling resistance) tubeless steel belted radial, all-season	S	S	S	S	S	S
	3TA	<b>Tires</b> , rear, LT215/85R16 E 115/112 L BW ALS VAR1, LRR (low rolling resistance) tubeless steel belted radial, all-season	S	S	S	S	S	S

2017 Chevrolet Truck 3500 LCF Gas STANDARD EQUIPMENT

Free Flow RPO Code	Ref. Only RPO Code	Description	Reg. Cab				Crew Cab	
			CP11003 109" WB 1WT	CP12003 132.5" WB 1WT	CP13003 150" WB 1WT	CP14003 176" WB 1WT	CP13043 150" WB 1WT	CP14043 176" WB 1WT
	PWJ	<b>Wheels</b> , 16" x 6, K. steel	S	S	S	S	S	S
	CD7	<b>Windshield wiper</b> , pulse, wet arm	S	S	S	S	S	S
	RQ2	<b>Vehicle Application Truck</b>	S	S	S	S	S	S
	VXT	<b>Incomplete vehicle certification</b>	S	S	S	S	S	S
	K45	<b>Air cleaner</b> , heavy-duty, 11" diameter dry paper single element. Air cleaner canister standard with air restriction gauge. Back of cab location.	S	S	S	S	S	S
	TP6	<b>Battery</b> , 750 cold-cranking amps, 12-volt single, maintenance free, frame-mounted battery box	S	S	S	S	S	S
	JE5	<b>Brakes</b> , 4-wheel antilock, front disc, rear drum, dual circuit, vacuum assisted hydraulic with EBD (Electronic Brake Distribution). Disc front and self-adjust outboard mounted drum rear. Mechanical, transmission-mounted parking brake. Non-asbestos semi-metallic linings are standard. 4 channel anti-lock brake system.	S	S	S	S	S	S
	J69	<b>Brake</b> , parking, cable actuated, internal expanding drum type, transmission-mounted	S	S	S	S	S	S
	L96	<b>Engine</b> , Vortec 6.0L V8 SFI, GMPT-V8 8 cylinder V block, four cycle overhead valve water cooled Vortec 6.0L SFI V8 297 hp [221.5 kW] @ 4300 rpm, 372 lb-ft of torque [504.0 N-m] @ 4000 rpm. Electronically-controlled sequential fuel injection. Six bolt main cap design for heavy-duty performance. Engine Control Module (ECM) and Transmission Control Module (TCM) engine control system. Engine cruise control, engine oil cooler, High Idle Mode (1200 rpm)	S	S	S	S	S	S
	N4C	<b>Emissions</b> , 50 state certification	S	S	S	S	S	S
	NB5	<b>Exhaust</b> , single outlet	S	S	S	S	S	S
	NH2	<b>Fuel tank</b> , 30 Gallon, (113L), rectangular fuel tank. mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill	S	S	S	S	S	S
	KG3	<b>Alternator</b> , 145 amps output with integral regulator	S	S	S	S	S	S
	C7L	<b>GVWR</b> , 12,000 lbs. (5443 kg)	S	S	S	S	S	S
	EB4	<b>Wheelbase</b> , 109" (276.9 cm)	S	--	--	--	--	--
	ED6	<b>Wheelbase</b> , 132.5" (336.6 cm)	--	S	--	--	--	--
	FWH	<b>Wheelbase</b> , 150" (381.0 cm)	--	--	S	--	S	--
	FNW	<b>Wheelbase</b> , 176" (447.0 cm)	--	--	--	S	--	S

2017 Chevrolet Truck 3500 LCF Gas STANDARD EQUIPMENT

Free Flow RPO Code	Ref. Only RPO Code	Description	Reg. Cab				Crew Cab	
			CP11003 109" WB 1WT	CP12003 132.5" WB 1WT	CP13003 150" WB 1WT	CP14003 176" WB 1WT	CP13043 150" WB 1WT	CP14043 176" WB 1WT
		<b>Frame</b> , ladder-type channel frame. Full C section straight frame 33.5" (85.1 cm) wide. Yield strength 44,000 psi, section modulus 7.20 cu.in. and RBM 316,800 lb-ft/in per rail.	S	S	S	S	S	S
	FL5	<b>Front axle</b> , 6,830 lbs. (3098 kg), reverse Elliot "I"-beam includes integral hydraulic power steering. ratio 18.8-20.9:1	S	S	S	S	S	S
	FM2	<b>Front suspension</b> , 8,440 lbs. (3828 kg) tapered leaf, semi-elliptical steel alloy tapered leaf springs. Includes shock absorbers and stabilizer bar.	S	S	S	S	S	S
	HS6	<b>Rear axle</b> , 11,020 lbs. (4998 kg) R050, full-floating single-speed, with oil lubricated rear wheel-bearings	S	S	S	S	S	S
	FU4	<b>Rear suspension</b> , 12,900 lbs. (5851 kg), multi-leaf, semi-elliptical steel alloy. Includes shock absorbers	S	S	S	S	S	S
	062	<b>Rear axle</b> , 5.12 ratio	S	S	S	S	S	S
	MYD	<b>Transmission</b> , 6-speed automatic, 6L90-E Hydra-Matic with lock-up converter and overdrive. Ratios: Gear and Ratios 4.027, 2.364, 1.532, 1.152, 0.852, 0.667, Rev. 3.064:1	S	S	S	S	S	S

**2017 Chevrolet Truck 3500 LCF Gas INTERIOR**

S = Standard Equipment A = Available -- (dashes) = Not Available D = ADI Available  
 ■ = Included in Equipment Group □ = Included in Equipment Group but upgradeable

\*Indicates availability of feature on multiple models. For example, it indicates feature availability on 2WD and 4WD Models or Rear wheel drive and All-wheel drive Models.

Codes listed in the shaded column titled Ref. Only RPO Code are for internal use only and should not be ordered.

Free Flow RPO Code	Ref. Only RPO Code	Description	Reg. Cab				Crew Cab	
			CP11003 109" WB 1WT	CP12003 132.5" WB 1WT	CP13003 150" WB 1WT	CP14003 176" WB 1WT	CP13043 150" WB 1WT	CP14043 176" WB 1WT
	C60	<b>Air conditioning</b> , single-zone manual, integral in-dash mounted	S	S	S	S	S	S
	K34	<b>Cruise control</b> , electronic, automatic	S	S	S	S	S	S
		<b>Cup holders</b>	S	S	S	S	S	S
	UIY	<b>Audio system</b> , AM/FM stereo with CD player, auxiliary input and USB Port	S	S	S	S	S	S
UIZ		<b>PIO, Audio System</b> , AM/FM stereo with CD player, auxiliary jack, USB port and Bluetooth, (Port Installed Option)	A	A	A	A	A	A
UL5		<b>PIO, Audio System</b> , radio delete, (Port Installed Option)	A	A	A	A	A	A
	UAD	<b>Audio system feature</b> , 2 speakers	S	S	S	S	S	S
	AU3	<b>Door locks</b> , power	S	S	S	S	S	S
	UDH	<b>Driver Information Center</b>	S	S	S	S	S	S
		<b>Floor mats</b>	S	S	S	S	S	S
MTE		<b>PIO, Fire extinguisher and safety reflector mounting provisions</b> , (Port Installed Option)	A	A	A	A	A	A
		<b>Lighting</b> , interior dome	S	S	S	S	S	S
IX2		<b>PIO, Rear dome and body lamp switch</b> , (Port Installed Option)	A	A	A	A	A	A
	A1F	<b>Seat</b> , front high back bucket driver and passenger, tricote cloth covered reclining highback driver seat with single two occupant fold down passenger seat	S	S	S	S	S	S
A1G		<b>PIO, Seat</b> , high back driver only air suspension seat and fixed passenger seat, (Port Installed Option) 1 - Not available with (9W8) protective seat-cover.	A <sup>1</sup>	A <sup>1</sup>	A <sup>1</sup>	A <sup>1</sup>	--	--
9W8		<b>PIO, Seat-cover protector</b> , (Port Installed Option) 1 - Not available with (A1G) high back driver air suspension seat.	A <sup>1</sup>	A <sup>1</sup>	A <sup>1</sup>	A <sup>1</sup>	A	A
	N3R	<b>Steering wheel</b> , urethane	S	S	S	S	S	S
	N33	<b>Steering column</b> , Tilt-Wheel	S	S	S	S	S	S
		<b>Storage</b> , door pockets	S	S	S	S	S	S
		<b>Storage</b> , seatback pockets	S	S	S	S	S	S

**2017 Chevrolet Truck 3500 LCF Gas INTERIOR**

Free Flow RPO Code	Ref. Only RPO Code	Description	Reg. Cab				Crew Cab	
			CP11003 109" WB 1WT	CP12003 132.5" WB 1WT	CP13003 150" WB 1WT	CP14003 176" WB 1WT	CP13043 150" WB 1WT	CP14043 176" WB 1WT
	A31	<b>Windows, power</b>	S	S	S	S	S	S
		<b>Windshield washer bottle access</b> , on passenger side dash when passenger-side door is open	S	S	S	S	S	S

**2017 Chevrolet Truck 3500 LCF Gas EXTERIOR**

S = Standard Equipment A = Available -- (dashes) = Not Available D = ADI Available  
 ■ = Included in Equipment Group □ = Included in Equipment Group but upgradeable

\*Indicates availability of feature on multiple models. For example, it indicates feature availability on 2WD and 4WD Models or Rear wheel drive and All-wheel drive Models.

Codes listed in the shaded column titled Ref. Only RPO Code are for internal use only and should not be ordered.

Free Flow RPO Code	Ref. Only RPO Code	Description	Reg. Cab				Crew Cab	
			CP11003 109" WB 1WT	CP12003 132.5" WB 1WT	CP13003 150" WB 1WT	CP14003 176" WB 1WT	CP13043 150" WB 1WT	CP14043 176" WB 1WT
		<b>Daytime Running Lamps</b>	S	S	S	S	S	S
		<b>Glass, tinted</b>	S	S	S	S	S	S
V22		<b>PIO, Grille, chrome, (Port Installed Option)</b>	A	A	A	A	A	A
	DB5	<b>Mirror, outside driver and front passenger, wide load with integral arm</b>	S	S	S	S	S	S
DB6		<b>PIO, Mirror, outside driver and front passenger, wide load, heated, power-adjustable, lighted with integral arm, (Port Installed Option)</b>	A	A	A	A	A	A
DB8		<b>PIO, Mirror, outside driver and front passenger, wide load, heated with integral arm, (Port Installed Option)</b>	A	A	A	A	A	A
XWL		<b>PIO, Mirror, provisions-bracket for 102" wide body, (Port Installed Option)</b>	A	A	A	A	A	A
UZF		<b>PIO, Back up alarm, (Port Installed Option)</b>	A	A	A	A	A	A
G7M		<b>PIO, Roof-air deflector</b>	A	A	A	A	--	--
PDI		<b>NEW! Pre-Delivery Inspection, Provides "Pre-Delivery Inspection" at the Port in cases where the vehicle needs to leave the port directly for the final stage manufacturing process and will not visit a dealer.</b>	A	A	A	A	A	A
	E01	<b>Assist steps</b>	S	S	S	S	S	S
	2TA	<b>Tires, front, LT215/85R16 E 115/112 L BW ALS VAR1, LRR (low rolling resistance) tubeless steel belted radial, all-season</b>	S	S	S	S	S	S
	3TA	<b>Tires, rear, LT215/85R16 E 115/112 L BW ALS VAR1, LRR (low rolling resistance) tubeless steel belted radial, all-season</b>	S	S	S	S	S	S
	PWJ	<b>Wheels, 16" x 6, K. steel</b>	S	S	S	S	S	S
	CD7	<b>Windshield wiper, pulse, wet arm</b>	S	S	S	S	S	S

**2017 Chevrolet Truck 3500 LCF Gas MECHANICAL**

S = Standard Equipment A = Available -- (dashes) = Not Available D = ADI Available  
 ■ = Included in Equipment Group □ = Included in Equipment Group but upgradeable

\*Indicates availability of feature on multiple models. For example, it indicates feature availability on 2WD and 4WD Models or Rear wheel drive and All-wheel drive Models.

Codes listed in the shaded column titled Ref. Only RPO Code are for internal use only and should not be ordered.

Free Flow RPO Code	Ref. Only RPO Code	Description	Reg. Cab				Crew Cab	
			CP11003 109" WB 1WT	CP12003 132.5" WB 1WT	CP13003 150" WB 1WT	CP14003 176" WB 1WT	CP13043 150" WB 1WT	CP14043 176" WB 1WT
	RQ2	<b>Vehicle Application Truck</b>	S	S	S	S	S	S
	VXT	<b>Incomplete vehicle certification</b>	S	S	S	S	S	S
	K45	<b>Air cleaner</b> , heavy-duty, 11" diameter dry paper single element. Air cleaner canister standard with air restriction gauge. Back of cab location.	S	S	S	S	S	S
	TP6	<b>Battery</b> , 750 cold-cranking amps, 12-volt single, maintenance free, frame-mounted battery box	S	S	S	S	S	S
	JE5	<b>Brakes</b> , 4-wheel antilock, front disc, rear drum, dual circuit, vacuum assisted hydraulic with EBD (Electronic Brake Distribution). Disc front and self-adjust outboard mounted drum rear. Mechanical, transmission-mounted parking brake. Non-asbestos semi-metallic linings are standard. 4 channel anti-lock brake system.	S	S	S	S	S	S
	J69	<b>Brake</b> , parking, cable actuated, internal expanding drum type, transmission-mounted	S	S	S	S	S	S
	L96	<b>Engine</b> , Vortec 6.0L V8 SFI, GMPT-V8 8 cylinder V block, four cycle overhead valve water cooled Vortec 6.0L SFI V8 297 hp [221.5 kW] @ 4300 rpm, 372 lb-ft of torque [504.0 N-m] @ 4000 rpm. Electronically-controlled sequential fuel injection. Six bolt main cap design for heavy-duty performance. Engine Control Module (ECM) and Transmission Control Module (TCM) engine control system. Engine cruise control, engine oil cooler, High Idle Mode (1200 rpm)	S	S	S	S	S	S
	LC8	<b>Engine</b> , 6.0L V8 SFI Gaseous	A	A	A	A	A	A
	N4C	<b>Emissions</b> , 50 state certification	S	S	S	S	S	S
	NB5	<b>Exhaust</b> , single outlet	S	S	S	S	S	S
	NH2	<b>Fuel tank</b> , 30 Gallon, (113L), rectangular fuel tank. mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill	S	S	S	S	S	S
	KG3	<b>Alternator</b> , 145 amps output with integral regulator	S	S	S	S	S	S
9C2		<b>PIO, Governor</b> , speed limited to 65-mph, (Port Installed Option)	A	A	A	A	A	A
	C7L	<b>GVWR</b> , 12,000 lbs. (5443 kg)	S	S	S	S	S	S

2017 Chevrolet Truck 3500 LCF Gas MECHANICAL

Free Flow RPO Code	Ref. Only RPO Code	Description	Reg. Cab				Crew Cab	
			CP11003 109" WB 1WT	CP12003 132.5" WB 1WT	CP13003 150" WB 1WT	CP14003 176" WB 1WT	CP13043 150" WB 1WT	CP14043 176" WB 1WT
	EB4	<b>Wheelbase</b> , 109" (276.9 cm)	S	--	--	--	--	--
	ED6	<b>Wheelbase</b> , 132.5" (336.6 cm)	--	S	--	--	--	--
	FWH	<b>Wheelbase</b> , 150" (381.0 cm)	--	--	S	--	S	--
	FNW	<b>Wheelbase</b> , 176" (447.0 cm)	--	--	--	S	--	S
		<b>Frame</b> , ladder-type channel frame. Full C section straight frame 33.5" (85.1 cm) wide. Yield strength 44,000 psi, section modulus 7.20 cu.in. and RBM 316,800 lb-ft/in per rail.	S	S	S	S	S	S
K05		<b>PIO, Engine block heater</b> , (Port Installed Option)	A	A	A	A	A	A
	FL5	<b>Front axle</b> , 6,830 lbs. (3098 kg), reverse Elliot "I"-beam includes integral hydraulic power steering. ratio 18.8-20.9:1	S	S	S	S	S	S
	FM2	<b>Front suspension</b> , 8,440 lbs. (3828 kg) tapered leaf, semi-elliptical steel alloy tapered leaf springs. Includes shock absorbers and stabilizer bar.	S	S	S	S	S	S
	HS6	<b>Rear axle</b> , 11,020 lbs. (4998 kg) R050, full-floating single-speed, with oil lubricated rear wheel-bearings	S	S	S	S	S	S
	FU4	<b>Rear suspension</b> , 12,900 lbs. (5851 kg), multi-leaf, semi-elliptical steel alloy. Includes shock absorbers	S	S	S	S	S	S
G86		<b>Axle</b> , limited slip	A	A	A	A	A	A
	062	<b>Rear axle</b> , 5.12 ratio	S	S	S	S	S	S
	MYD	<b>Transmission</b> , 6-speed automatic, 6L90-E Hydra-Matic with lock-up converter and overdrive. Ratios: Gear and Ratios 4.027, 2.364, 1.532, 1.152, 0.852, 0.667, Rev. 3.064:1	S	S	S	S	S	S



S = Standard Equipment    A = Available    -- (dashes) = Not Available  
 ■ = Included in Equipment Group    □ = Included in Equipment Group but upgradeable

\*Indicates availability of feature on multiple models. For example, it indicates feature availability on 2WD and 4WD Models or Rear wheel drive and All-wheel drive Models.

Decor Level	Seat Type	Seat Code	Seat Trim	Interior
				Very Dark Pewter
1WT	High back bucket seat	A1F	Cloth	HNF
1WT	High back bucket air suspension seat	A1G	Cloth	HNF

Exterior Solid Paint	Color Code	Touch Up Paint Number	Interior
			Very Dark Pewter
Arc White	16U	WA-none	A

All dimensions in inches (mm) unless otherwise stated.

	Specifications	CP11003	CP12003	CP13003	CP14003	
		12,000 lb. GVWR Gas 109" Wheelbase Regular Cab	12,000 lb. GVWR Gas 132.5" Wheelbase Regular Cab	12,000 lb. GVWR Gas 150" Wheelbase Regular Cab	12,000 lb. GVWR Gas 176" Wheelbase Regular Cab	
	A	<b>Wheelbase</b>	109.00 (2769)	132.50 (3366)	150.00 (3810)	176.00 (4470)
	B	<b>Overall length</b>	200.50 (5093)	224.00 (5690)	241.50 (6134)	267.50 (6794)
		<b>Overall width</b>	81.30 (2065)	81.30 (2065)	81.30 (2065)	81.30 (2065)
	D	<b>Overall height</b>	90.00 (2286)	90.00 (2286)	90.00 (2286)	90.00 (2286)
		<b>Rear track width</b>	65.60 (1666)	65.60 (1666)	65.60 (1666)	65.60 (1666)
	CA	<b>Cab to axle</b>	86.50 (2197)	110.00 (2794)	127.50 (3238)	153.50 (3899)
		<b>Cab to end of frame</b>	129.60 (3292)	153.10 (3889)	170.60 (4333)	196.60 (4994)
		<b>Frame width, rear</b>	33.50 (851)	33.50 (851)	33.50 (851)	33.50 (851)

Published dimensions indicated are without optional equipment or accessories. Additional accessories or equipment ordered at the customer's request can result in a minor change in these dimensions.

All dimensions in inches (mm) unless otherwise stated.

		Specifications	CP13043 12,000 lb. GVWR Gas 150" Wheelbase Crew Cab	CP14043 12,000 lb. GVWR Gas 176" Wheelbase Crew Cab
	A	<b>Wheelbase</b>	150.00 (3810)	176.00 (4470)
	B	<b>Overall length</b>	241.50 (6134)	267.50 (6794)
		<b>Overall width</b>	81.30 (2065)	81.30 (2065)
	D	<b>Overall height</b>	90.00 (2286)	90.00 (2286)
		<b>Rear track width</b>	65.60 (1666)	65.60 (1666)
	CA	<b>Cab to axle</b>	88.50 (2248)	114.50 (2908)
		<b>Cab to end of frame</b>	131.60 (3343)	157.60 (4003)
		<b>Frame width, rear</b>	33.50 (851)	33.50 (851)

Published dimensions indicated are without optional equipment or accessories. Additional accessories or equipment ordered at the customer's request can result in a minor change in these dimensions.

	CP11003 12,000 lb. GVWR Gas 109" Wheelbase Regular Cab	CP12003 12,000 lb. GVWR Gas 132.5" Wheelbase Regular Cab	CP13003 12,000 lb. GVWR Gas 150" Wheelbase Regular Cab	CP14003 12,000 lb. GVWR Gas 176" Wheelbase Regular Cab
<b>Specifications</b>				
Frame Material Strength (psi)	44000	44000	44000	44000
Frame Section Modulus (in <sup>2</sup> )	7.20	7.20	7.20	7.20
Frame RBM (lb-ft/in)	316800	316800	316800	316800
Body length available (ft.)	10-12	14	16-18	20
<b>Capacities</b>				
Payload <sup>1</sup> , lbs. (kg)	6782 (3076)	6782 (3076)	6782 (3076)	6782 (3076)
Gross Combination Maximum Rating (GCMR), lbs. (kg)	18000 (8165)	18000 (8165)	18000 (8165)	18000 (8165)
Gross Vehicle Weight Rating, lbs. (kg)	12000 (5443)	12000 (5443)	12000 (5443)	12000 (5443)
Fuel capacity, Imperial, gallon (liters)	30.0 (136)	30.0 (136)	30.0 (136)	30.0 (136)
1. Maximum payload capacity includes weight of driver, passengers, optional equipment and cargo.				

	CP13043 12,000 lb. GVWR Gas 150" Wheelbase Crew Cab	CP14043 12,000 lb. GVWR Gas 176" Wheelbase Crew Cab
<b>Specifications</b>		
Frame Material Strength (psi)	44000	44000
Frame Section Modulus (in <sup>2</sup> )	7.20	7.20
Frame RBM (lb-ft/in)	316800	316800
Body length available (ft.)	12	14
<b>Capacities</b>		
Payload <sup>2</sup> , lbs. (kg)	6782 (3076)	6782 (3076)
Gross Combination Maximum Rating (GCMR), lbs. (kg)	18000 (8165)	18000 (8165)
Gross Vehicle Weight Rating, lbs. (kg)	12000 (5443)	12000 (5443)
Fuel capacity, Imperial, gallon (liters)	30.0 (136)	30.0 (136)
2. Maximum payload capacity includes weight of driver, passengers, optional equipment and cargo.		

Option Code	Description
IX2	PIO, Rear dome and body lamp switch
062	Rear axle, 5.12 ratio
2TA	Tires, front, LT215/85R16 E 115/112 L BW ALS VAR1
3TA	Tires, rear, LT215/85R16 E 115/112 L BW ALS VAR1
9C2	PIO, Governor, speed limited to 65-mph
9W8	PIO, Seat-cover protector
A1F	Seat, front high back bucket driver and passenger
A1G	PIO, Seat, high back driver only air suspension seat and fixed passenger seat
A31	Windows, power
AU3	Door locks, power
C60	Air conditioning, single-zone manual
C7L	GVWR, 12,000 lbs. (5443 kg)
CD7	Windshield wiper, pulse, wet arm
DB5	Mirror, outside driver and front passenger, wide load with integral arm
DB6	PIO, Mirror, outside driver and front passenger, wide load, heated, power-adjustable, lighted with integral arm
DB8	PIO, Mirror, outside driver and front passenger, wide load, heated with integral arm
E01	Assist steps
EB4	Wheelbase, 109" (276.9 cm)
ED6	Wheelbase, 132.5" (336.6 cm)
FL5	Front axle, 6,830 lbs. (3098 kg)
FM2	Front suspension, 8,440 lbs. (3828 kg) tapered leaf
FNW	Wheelbase, 176" (447.0 cm)
FU4	Rear suspension, 12,900 lbs. (5851 kg), multi-leaf
FWH	Wheelbase, 150" (381.0 cm)
G7M	PIO, Roof-air deflector
G86	Axle, limited slip
HS6	Rear axle, 11,020 lbs. (4998 kg)
J69	Brake, parking
JE5	Brakes, 4-wheel antilock, front disc, rear drum
K05	PIO, Engine block heater
K34	Cruise control
K45	Air cleaner, heavy-duty
KG3	Alternator, 145 amps
L96	Engine, Vortec 6.0L V8 SFI
LC8	Engine, 6.0L V8 SFI Gaseous
MTE	PIO, Fire extinguisher and safety reflector mounting provisions
MYD	Transmission, 6-speed automatic
N33	Steering column, Tilt-Wheel
N3R	Steering wheel, urethane
N4C	Emissions, 50 state certification
NB5	Exhaust, single outlet
NH2	Fuel tank, 30 Gallon, (113L)
PDI	Pre-Delivery Inspection, Provides "Pre-Delivery Inspection" at the Port in cases where the vehicle needs to leave the port directly for the final stage manufacturing process and will not visit a dealer.
PWJ	Wheels, 16" x 6, K. steel
RQ2	Vehicle Application Truck
TP6	Battery, 750 cold-cranking amps, 12-volt single

Option Code	Description
UAD	Audio system feature, 2 speakers
UDH	Driver Information Center
UIY	Audio system, AM/FM stereo with CD player
UIZ	PIO, Audio System, AM/FM stereo with CD player
UL5	PIO, Audio System, radio delete
UZF	PIO, Back up alarm
V22	PIO, Grille, chrome
VXT	Incomplete vehicle certification
XWL	PIO, Mirror, provisions-bracket for 102" wide body

## Updates for 3500 LCF Gas

### Week of 5/9/2016

Effective 5/9/2016, the following changes will be made to the Vehicle Order Guide:

- Exterior section-Added (PDI) Pre-Delivery Inspection, Provides "Pre-Delivery Inspection" at the Port in cases where the vehicle needs to leave the port directly for the final stage manufacturing process and will not visit a dealer. This option has "A" availability on all trims.

### Week of 5/2/2016

Effective 5/2/2016, the following changes will be made to the Vehicle Order Guide:

- Front page added "Not available to order at this time." on all models.

### Week of 4/18/2016

Effective 4/18/2016, the following changes will be made to the Vehicle Order Guide:

- Mechanical section-(ED6) Wheelbase, 132" (335.3 cm), updated extended description to read "132.5" (336.6)".

### Week of 4/11/2016

Effective 4/11/2016, the following changes will be made to the Vehicle Order Guide:

- Color and Trim section-(16U) White, changed name to "Arc White".